


PK5A7BA

P-Channel Logic Level Enhancement Mode MOSFET


PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
-20V	3.5mΩ @ $V_{GS} = -10V$	-108A



PDFN 5x6P

100% UIS Tested
100% Rg Tested



ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ °C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	-20	V
Gate-Source Voltage		V_{GS}	±12	
Continuous Drain Current ⁴	$T_C = 25\text{ °C}$	I_D	-108	A
	$T_C = 100\text{ °C}$		-68	
	$T_A = 25\text{ °C}$		-24	
	$T_A = 70\text{ °C}$		-19	
Pulsed Drain Current ¹		I_{DM}	-200	
Avalanche Current		I_{AS}	-53	
Avalanche Energy	L = 0.1mH	E_{AS}	140	mJ
Power Dissipation ³	$T_C = 25\text{ °C}$	P_D	69	W
	$T_C = 100\text{ °C}$		27	
	$T_A = 25\text{ °C}$		3.5	
	$T_A = 70\text{ °C}$		2.2	
Operating Junction & Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

PK5A7BA

P-Channel Logic Level Enhancement Mode MOSFET

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE		SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Ambient ²	$t \leq 10s$	$R_{\theta JA}$		35	°C / W
Junction-to-Ambient ²	Steady-State	$R_{\theta JA}$		50	
Junction-to-Case	Steady-State	$R_{\theta JC}$		1.8	

¹Pulse width limited by maximum junction temperature.

²The value of $R_{\theta JA}$ is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ C$. The value in any given application depends on the user's specific board design.

³The Power dissipation is based on $R_{\theta JA}$ $t \leq 10s$ value.

⁴Package limitation current is 50A.

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ C$, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-0.6	-0.7	-1.1	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 12V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -16V, V_{GS} = 0V$			-1	uA
		$V_{DS} = -10V, V_{GS} = 0V, T_J = 125^\circ C$			-10	
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = -10V, I_D = -20A$		2.6	3.5	mΩ
		$V_{GS} = -4.5V, I_D = -20A$		3.1	4	
		$V_{GS} = -2.5V, I_D = -20A$		4.3	5.7	
Forward Transconductance ¹	g_{fs}	$V_{DS} = -5V, I_D = -20A$		50		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = -10V, f = 1MHz$		6383		pF
Output Capacitance	C_{oss}			927		
Reverse Transfer Capacitance	C_{rss}			793		
Gate Resistance	R_g	$V_{GS} = 0V, V_{DS} = 0V, f = 1MHz$		3		Ω
Total Gate Charge ²	Q_g	$V_{DS} = -10V,$ $V_{GS} = -10V, I_D = -20A$		161		nC
Gate-Source Charge ²	Q_{gs}			6.3		
Gate-Drain Charge ²	Q_{gd}			21		
Turn-On Delay Time ²	$t_{d(on)}$	$I_D \cong -20A, V_{GS} = -10V, R_{GS} = 6\Omega$		13		nS
Rise Time ²	t_r			12		
Turn-Off Delay Time ²	$t_{d(off)}$			350		
Fall Time ²	t_f			136		

PK5A7BA

P-Channel Logic Level Enhancement Mode MOSFET

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T_J = 25 °C)


Continuous Current	I _S				-53	A
Forward Voltage ¹	V _{SD}	I _F = -20A, V _{GS} = 0V			-1.3	V
Reverse Recovery Time	t _{rr}	I _F = -20A, dI _F /dt = 100A / μS		75		nS
Reverse Recovery Charge	Q _{rr}			61		nC

¹Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

²Independent of operating temperature.

PK5A7BA


P-Channel Logic Level Enhancement Mode MOSFET




PK5A7BA

P-Channel Logic Level Enhancement Mode MOSFET


Gate charge Characteristics




Source-Drain Diode Forward Voltage




Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve




PK5A7BA

P-Channel Logic Level Enhancement Mode MOSFET

Package Dimension

PDFN 5x6P MECHANICAL DATA


Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	4.8		5.15	J	3.34		3.9
B	5.42		5.9	K	0.9		
C	5.9		6.35	L	0.38		0.711
D	0.3		0.51	M	0°		12°
E	1.17	1.27	1.37	N	4.8		5.4
F	0.8	1	1.2	O	0.05		0.36
G	0.15		0.35	P	0.05		0.25
H	3.67		4.31	S	3.73		4.19
I	0.38		0.71				




PK5A7BA

P-Channel Logic Level Enhancement Mode MOSFET

A. Marking Information




B. Tape & Reel Information: 3000pcs/Reel




PK5A7BA
P-Channel Logic Level Enhancement Mode MOSFET

C. Lot No.&Date Code rule

1. Lot No.



2. Date Code





PK5A7BA

P-Channel Logic Level Enhancement Mode MOSFET

D.Label rule

标签内容(Label content)



1	Label Size	30 * 90 mm
2	Font style	Times New Roman or Arial (或可区分英文"0"和数字"0", "G"和"Q"的字型即可)
3	U-NIKC	Height: 4 mm
4	Package	Height: 2 mm
5	Date	Height: 2 mm Shipping date: YYYY/MM/DD, ex. 2008/09/12
6	Device	Height: 3 mm (Max: 16 Digit)
7	Lot	Height: 3 mm (Max: 9 Digit) Sub lot
8	D/C	Height: 3 mm (Max: 7 Digit)
9	QTY	Height: 3 mm (Max: 6 Digit) Thousand mark is no needed
10	RoHS label	 long axis: 12 mm minor axis: 6 mm bottom color: White Font color: Black Font style: Arial
11	Halogen Free label	 Diameter: 10 mm bottom color: Green Font color: Black Font style: Arial
12	Scan information	Device / Lot / D/C / QTY , Insert "/" between every parts. for example: P3055LDG/G12345601/GGG2301/2000 DPI (Dots per inch): Over 300 dpi Code : Code 128 Height: 6 mm at least