



PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
-30	45m	-4A



- 1. GATE
- 2. DRAIN
- 3. SOURCE

ABSOLUTE MAXIMUM RATINGS ($T_C = 25\text{ }^\circ\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current	$T_C = 25\text{ }^\circ\text{C}$	I_D	-4	A
	$T_C = 70\text{ }^\circ\text{C}$		-3	
Pulsed Drain Current ¹		I_{DM}	-20	
Power Dissipation	$T_C = 25\text{ }^\circ\text{C}$	P_D	0.78	W
	$T_C = 70\text{ }^\circ\text{C}$		0.62	
Operating Junction & Storage Temperature Range		T_{j}/T_{stg}	-55 to 150	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		18	$^\circ\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		160	$^\circ\text{C} / \text{W}$

¹Pulse width limited by maximum junction temperature.

²Duty cycle $\leq 1\%$

ELECTRICAL CHARACTERISTICS ($T_C = 25\text{ }^\circ\text{C}$, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-0.9	-1.5	-3	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -24V, V_{GS} = 0V$			1	μA
		$V_{DS} = -20V, V_{GS} = 0V, T_J = 125\text{ }^\circ\text{C}$			10	
On-State Drain Current ¹	$I_{D(ON)}$	$V_{DS} = -5V, V_{GS} = -10V$	-20			A
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = -4.5V, I_D = -3A$		60	75	m
		$V_{GS} = -10V, I_D = -4A$		37	45	
Forward Transconductance ¹	g_{fs}	$V_{DS} = -10V, I_D = -4A$		16		S

DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = -15V, f = 1MHz$		530		pF
Output Capacitance	C_{oss}			135		
Reverse Transfer Capacitance	C_{rss}			70		
Total Gate Charge ²	Q_g	$V_{DS} = 0.5V_{(BR)DSS}, V_{GS} = -10V,$ $I_D = -4A$		10	14	nC
Gate-Source Charge ²	Q_{gs}			2.2		
Gate-Drain Charge ²	Q_{gd}			2		
Turn-On Delay Time ²	$t_{d(on)}$	$V_{DS} = -15V,$ $I_D \cong -1A, V_{GS} = -10V, R_{GS} = 6$		5.7		nS
Rise Time ²	t_r			10		
Turn-Off Delay Time ²	$t_{d(off)}$			18		
Fall Time ²	t_f			5		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS ($T_C = 25^\circ C$)						
Continuous Current	I_S				-2.1	A
Pulsed Current ³	I_{SM}				-4	
Forward Voltage ¹	V_{SD}	$I_F = -1A, V_{GS} = 0V$			-1.2	V
Reverse Recovery Time	t_{rr}	$I_F = -4A, di_F/dt = 100A / \mu S$		15.5		nS
Reverse Recovery Charge	Q_{rr}			7.9		nC

¹Pulse test : Pulse Width $\leq 300 \mu sec$, Duty Cycle $\leq 2\%$.

²Independent of operating temperature.







³Pulse width limited by maximum junction temperature.






REMARK: THE PRODUCT MARKED WITH "P06P03G", DATE CODE or LOT #

Orders for parts with Lead-Free plating can be placed using the PXXXXXXG parts name.

CONFIDENTIAL

Typical Characteristics





SOT-89 MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	4.3	4.5	4.7	H	1.4	1.5	1.6
B	1.6	1.7	1.8	I	2.8	3.0	3.2
C	0.4	0.5	0.6	J	1.3	1.5	1.7
D	2.4	2.5	2.6	K	3.8	4.2	4.6
E	0.8	1.2	1.4	L	0.3	0.4	0.5
F	0.4	0.45	0.5	M			
G	0.4	0.5	0.6	N			

