



PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
25	13.8m Ω	60A



1. GATE
2. DRAIN
3. SOURCE

ABSOLUTE MAXIMUM RATINGS ($T_C = 25\text{ }^\circ\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current	$T_C = 25\text{ }^\circ\text{C}$	I_D	60	A
	$T_C = 100\text{ }^\circ\text{C}$		36	
Pulsed Drain Current ¹		I_{DM}	140	
Avalanche Current		I_{AR}	20	
Avalanche Energy	$L = 0.1\text{mH}$	E_{AS}	140	mJ
	$L = 0.05\text{mH}$	E_{AR}	5.6	
Power Dissipation	$T_C = 25\text{ }^\circ\text{C}$	P_D	60	W
	$T_C = 100\text{ }^\circ\text{C}$		38	
Operating Junction & Storage Temperature Range		T_J, T_{stg}	-55 to 150	$^\circ\text{C}$
Lead Temperature (¹ / ₁₆ " from case for 10 sec.)		T_L	275	

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		3	$^\circ\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		70	
Case-to-Heatsink	$R_{\theta CS}$	0.7		

¹Pulse width limited by maximum junction temperature.²Duty cycle $\leq 1\%$ ELECTRICAL CHARACTERISTICS ($T_C = 25\text{ }^\circ\text{C}$, Unless Otherwise Noted)

ELECTRICAL CHARACTERISTICS (T _J = 25 °C, unless otherwise noted)						
PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	25			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	0.8	1.2	2.5	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0V, V _{GS} = ±20V			±250	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20V, V _{GS} = 0V			25	μA
		V _{DS} = 20V, V _{GS} = 0V, T _J = 125 °C			250	

On-State Drain Current ¹	I _{D(ON)}	V _{DS} = 10V, V _{GS} = 10V	60			A
Drain-Source On-State Resistance ¹	R _{DS(ON)}	V _{GS} = 7V, I _D = 20A		13.5	17.8	mΩ
		V _{GS} = 10V, I _D = 22A		10.5	13.8	
Forward Transconductance ¹	g _{fs}	V _{DS} = 15V, I _D = 30A		16		S
DYNAMIC						
Input Capacitance	C _{iss}	V _{GS} = 0V, V _{DS} = 15V, f = 1MHz		600		pF
Output Capacitance	C _{oss}			290		
Reverse Transfer Capacitance	C _{rss}			100		
Total Gate Charge ²	Q _g	V _{DS} = 10V, V _{GS} = 10V, I _D = 22A		30		nC
Gate-Source Charge ²	Q _{gs}			2.9		
Gate-Drain Charge ²	Q _{gd}			7.0		
Turn-On Delay Time ²	t _{d(on)}	V _{DS} = 15V, R _L = 1Ω I _D ≅ 30A, V _{GS} = 10V, R _{GS} = 2.5Ω		7.0		nS
Rise Time ²	t _r			7.0		
Turn-Off Delay Time ²	t _{d(off)}			24		
Fall Time ²	t _f			6.0		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T _c = 25 °C)						
Continuous Current	I _S				60	A
Pulsed Current ³	I _{SM}				140	
Forward Voltage ¹	V _{SD}	I _F = I _S , V _{GS} = 0V			1.3	V
Reverse Recovery Time	t _{rr}	I _F = I _S , di _F /dt = 100A / μS		37		nS
Peak Reverse Recovery Current	I _{RM(REC)}			200		A
Reverse Recovery Charge	Q _{rr}			0.043		μC

¹Pulse test : Pulse Width $\leq 300 \mu sec$, Duty Cycle $\leq 2\%$.


²Independent of operating temperature.

³Pulse width limited by maximum junction temperature.


REMARK: THE PRODUCT MARKED WITH "P60N03LDG", DATE CODE or LOT #
Orders for parts with Lead-Free plating can be placed using the PXXXXXXXG parts name.

TYPICAL CHARACTERISTICS


ON-REGION CHARACTERISTIC




ON-RESISTANCE VARIATION WITH DRAIN CURRENT AND GATE




ON-RESISTANCE VARIATION WITH TEMPERATURE




ON-RESISTANCE VARIATION WITH GATE-TO-SOURCE VOLTAGE








TRANSFER CHARACTERISTICS



BODY DIODE FORWARD VOLTAGE VARIATION WITH SOURCE CURRENT AND TEMPERATURE





TO-252 (DPAK) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	9.35		10.4	H	0.89		2.03
B	2.2		2.4	I	6.35		6.80
C	0.45		0.6	J	5.2		5.5
D	0.89		1.5	K	0.6		1.5
E	0.45		0.69	L	0.5		0.9
F	0.03		0.23	M	3.96	4.57	5.18
G	5.2		6.2	N			

